

Mounting **Mounting Flange Kit**

Mounting Flange Kit for Polycarbonate Enclosures 8 Inch



**Catalog
Number**

MFK8

UPC

785928579998.0

List Price

\$38.19

DESCRIPTION

8 Inch Mounting Flange Kit for polycarbonate enclosures are designed as a robust mounting option. They are ideal for non-hazardous industrial and commercial applications and are commonly used in electrical control, measurement and monitoring, security, oil and gas, manufacturing, and communications. They feature an innovative mounting cross which allows for multiple screw positions. Additionally, the flange can be mounted on the top and bottom, or sides of the enclosure. They feature a water-shedding flange design contains a built-in radius to prevent accumulation of water. Hardware is included.



FEATURES

- Robust, corrosion resistant polycarbonate construction
- Innovative curved water shedding design surface allows

for water run off

- Self-seating mounting feature allows for ease of installation
- Flexible design can be mounted in either vertical or horizontal position on enclosure
- Hardware included
- Available as standalone SKUs or included with our enclosures

General Information

| | |
|--|------------------|
| Color | Gray |
| Material | Polycarbonate |
| Mounting Flange Screw Material | 304 SS |
| Mounting Flange Screw Size | 1/4-20 x 1/2 |
| Mounting Flange Screw Recommended Torque | 10-14 in-lbs |
| Installation Mounting Torque | 25-30 in-lbs Max |
| Country of Origin | India |

DIMENSIONS

| | |
|-------------|-------|
| Height (in) | 3.3 |
| Width (in) | 6.9 |
| Depth (in) | 0.5 |
| Height (mm) | 82.6 |
| Width (mm) | 175.0 |
| Depth (mm) | 12.7 |

STANDARDS

| | |
|-------------------------|-----------------|
| Temperature Range °F | -40°F to +248°F |
| Temperature Range °C | -40°C to +120°C |
| Flammability Rating | UL94-5VA |
| Outdoor Exposure UL746c | (f1) Rated |