

Enclosures JW Series

Fiberglass Enclosure 18 x 16 x 17 Inches Fatboy Series with Window and Hinged, Latched Opaque Cover

CULUSTED US ISO JOOI



 Catalog
 JW181617SSH

 Number
 785928102394.0

List Price **\$0.00**


DESCRIPTION

18H x 16W x 17D Inches Fatboy Series Fiberglass Enclosure with an "WSSH" Flush Bonded Window Cover (Hinged, Padlock Latches) is a clam shell style enclosure, noted by near equidistant capactiy in both the cover and the base. The Fatboy Series offers an extra deep enclosure without significatly increasing the height and width of the enclosure. The series has a flange mount base for east of installation, a stainless steel full length hinge and stainless steel securing latch.

APPLICATION

Industrial enclosure for harsh; aggressive environments

FEATURES



Enclosures



Enclosures

- •Clam shell design; opening from the middle of the enclosure
- Increased wall thickness vs. competitive models offers structural support and prevents potential water ingress
- •Integral mounting flange vs. mounting feet (no assembly required)
- Molded-in inserts provide added pull-out strength
- Flush-bonded Window Cover
- Overhang cover on smooth sided base
- High temperature; flame retardant; non-corrosive
- •All stainless hardware latches and screws
- Full-length; stainless-steel hinge
- Chemically resistant; fiberglass reinforced polyester
- •Non-corrosive; environmental designs
- Stainless steel retention chain on screw covers
- Continuous polyurethane gasket
- Manufactured with SolarGuard®, Stahlin's proprietary formulation of non-halogenated fiberglass, offering superior resistance to outdoor exposure, chemicals and flames.
- Back Panels Available for all sizes

General Information

Color	Gray
Cover Type	Window
Material	Fiberglass
Back Panel Screw Size	#10-32 x 3/8
Back Panel Recommended Torque	16-20 in-lbs
Back Panel Screw Material	304 SS
Installation Mounting Torque	45 in-lbs Max
Metal Inserts	Brass
Hinge Material	304 SS
Latch Material	304 SS
Gasket Material	Poured In Place (PIP) Polyurethane Seamless
Country of Origin	USA



Enclosures

DIMENSIONS

Height (in)	19.6
Width (in)	16.9
Depth (in)	17.2
Height (mm)	498.6
Width (mm)	429.8
Depth (mm)	436.6
Usable Depth (in)	16.4
Usable Depth (mm)	416.0

STANDARDS

NEMA 10250; UL 50; UL 50e; UL508A	cULus Listed File #E64358
CSA Std. C22.2	cULus Listed File #E64358
Туре	1; 3R; 4; 4X; 12
IEC 60529; UL Listed #E362920	IP66
UL1741	UL Listed File #E333478
Plenum Space UL2043	Compliant
Temperature Range °F	-76°F to +274°F
Temperature Range °C	-60°C to +134°C
Window Temperature Range °F	-26°F to +170°F
Window Temperature Range °C	-32°C to +76°C
Flammability Rating	UL94-5VA
NFPA No. 101 Flame Spread	Class A(1)
Outdoor Exposure UL746c	(f1) Rated
CE	Certified