



Enclosures Starke Series

Polycarbonate Enclosure Small 6 \times 5 \times 2 Inches Starke Series with Clear Lift Off Cover







Catalog Number STCC161255W

UPC

785928572005

DESCRIPTION

6H x 5W x 2D Inches Starke Series Small Polycarbonate Enclosure with Clear (STCC) Screw Cover (4 Cover Screws, Lift-off Configuration) features flush sides making it ideal for OEM designed product. Raised bosses accommodate back panel mounting and are used for remote sensor mounting and small electronic controls in any environment.

APPLICATION

- Small; simple design ideal for OEMs in the electronics market; circuit boards and wiring applications
- •Used for remote sensor mounting and small electronic controls in any environment
- Used indoors or outdoors
- Used in highly corrosive areas

FEATURES









- •Clear Cover
- Multiple depths available in most sizes
- Resistant to harsh environments
- Flush sides for that perfect fit
- Multiple molded in bosses for a variety of mounting solutions
- Back Panels Available for all sizes

General Information

| Gray |
|--|
| Clear |
| Wall Mount |
| Polycarbonate |
| Plastite 48 #8 |
| 12-16 in-lbs |
| 304 SS |
| 304 SS |
| 25-30 in-lbs Max |
| Brass |
| Poured In Place (PIP) Polyurethane Seamless |
| Germany |
| |

DIMENSIONS

| Height (in) | 6.0 |
|-------------------|-------|
| Width (in) | 5.0 |
| Depth (in) | 2.0 |
| Height (mm) | 152.4 |
| Width (mm) | 127.0 |
| Depth (mm) | 50.8 |
| Usable Depth (in) | 1.7 |
| Usable Depth (mm) | 42.0 |
| | |



Enclosures

STANDARDS

| NEMA 10250; UL 50; UL 50e; UL508A | cULus Listed File #E64358 |
|--------------------------------------|------------------------------|
| CSA Std. C22.2 | cULus Listed File #E64358 |
| Туре | 1; 3R; 4; 4X; 12 |
| IEC 60529; UL Listed #E362920 | IP66 |
| Temperature Range °F | -40°F to +212°F |
| Temperature Range °C | -40°C to +100°C |
| Flammability Rating | UL94-V2 |
| Outdoor Exposure UL746c | (f1) Rated |
| CE | Certified |