


4 MOUNTING FEET REQ'D. PER KIT



4 MOUNTING SCREWS REQ'D. PER KIT RMSC10-32x7/16FHPH SCREW 18-8 STAINLESS STEEL

<u>NOTES</u>

DIMENSIONS ARE SHOWN AS MOLDED.

DRAFT IS 1.5 DEGREES UNLESS SPECIFIED OTHERWISE.

ALL EDGES SHALL BE FILLETED EXCEPT BACK EDGE.

HOLE FILLET RADIUS IS 0.010"; OTHER EDGE FILLET RADIUS IS 0.030".

CRITICAL INSPECTION DIMENSIONS ARE WITHIN A BOX.

EJECTOR PINS TO BE FLUSH TO .010 BELOW SURFACE

VOLUME = 0.478 CU. IN.

NUTES

NUTES:											
	COLOR : GLACIER GRAY RR3013								TOLERANCES TWO PLACE THREE PLACE		
KIT INCLUDES INST. SHEET, SCREWS, MTG FT, SUITABLE PLASTIC BAG UNLESS SPE									TED ± .02	.005 ± .005	
MATERIAL: ISO POLYESTER SMC OR EQUIV RR3xxxx OR EQUIV UL746 APPROVED MATERIAL ZJB 11/26/02 STAHLIN BELDING MIC									DEL DING MICHICAN		
LET.	REVISION RECORD	DATE	BY	CHD.	CHK, BY	DATE		NCLOSURES		BELDING,MICHIGAN 48809	
A	UPDATED MATL. INFO. DIA WAS .22 ,WAS9/16	5/7/04 8/18/04	MJ MJ				CUSTOMER	IVISION OF ROBRDY INDUSTRIES	· ·		
В	SCREW DIA. WAS .48	8/18/04	LM		APD. BY	DATE		STAHLIN			
С	TOLERANCE ADDED TO Ø0.210	2/23/05	GF		SCALE D. N. S.			E ENCLOSURE ING FOOT KIT	PART NO	DSMGFTKIT	