



DETAIL A
 WINDOW MATERIAL: S.A.R. ACRYLIC, 1/4" THICK
 ABRASE INSIDE COVER SURFACE PRIOR TO BONDING
 WINDOW BONDED USING MA-320
 WINDOW SURFACE FLUSH TOLERANCE: +0.020 / -0.030
 0.010 MAX. EXPANSION GAP BETWEEN COVER CUTOUT & WINDOW

THIS DRAWING IS THE SOLE AND EXCLUSIVE PROPERTY OF STAHLIN AND OTHERS. NO PART OF THIS DRAWING MAY BE REPRODUCED, STORED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE EXPRESS WRITTEN PERMISSION OF STAHLIN INDUSTRIES. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS, COMPANIES AND PATENT OFFICES.

SPECIAL REQUIREMENTS

NEMA 250 TYPE 1, 3, 3R, 4X, 12, 13		STANDARD PIN:	JW100806HLL	ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED	TOLERANCES UNLESS SPECIFIED	XX ±0.03	XXX ±0.010
REF: 40259 (REV)		CUSTOMER DWG:					
COLOR: GLAZIER GRAY (IMPRESIT)				 STAHLIN A DIVISION OF ROBROY INDUSTRIES 500 Maple Street Belding, Michigan 48809 Phone: 616-794-2700 Fax: 616-749-3373			
COLOR STANDARDS: PANTONE 685C							
MATERIAL: FIBERGLASS REINFORCED POLYESTER (FRP)							
REVISION HISTORY							
REV	DESCRIPTION	DATE	ENG	DATE	DESCRIPTION	PART NUMBER	DWG
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-
SCALE: 2 NOT SCALE				DESCRIPTION: STANDARD ENCLOSURE		PART NUMBER: FEJW100806HLL	